




Fast Connector HH A04



Product Structure:

Measured the Structure



Product length: 50MM

Optical Characteristics:

Category	Specification
Applicable for	Drop cable. Indoor cable
Fiber mod	Single mode or Multi mode
Fiber type	G.652D, G.657A2,
Fiber cable	3.0*2.0mm rubber-insulated optical cable Ø3.0 /Ø0.9 insulated optical cab
Fiber diameter	0.125mm
Force holds 2 x 3mm cable type at the beginning the fast connector	≥ 45 N, loss ≤ 0.3 dB
Fiber lock	Lock holds fiber reliability, bears hang force ≥ 1.5 N, attenuation changes ≤ 0.2 dB
Working wavelength	1310 nm, 1490 nm, 1550 nm

Operation time	S	About 50(no fiber cut)
Insertion Loss	dB	≤0.35
Insertion Loss Typical value	dB	0.3
Return Loss	dB	UPC≥50, APC≥55
Fastening strength of naked fiber	N	≥3
Tensile strength	N	≥45
Reusable	Time	≥10 time
Operating Temperature		-40~+85
On-line tensile strength (20N)	dB	ΔIL≤0.3
Mechanical durability (500 times)	dB	ΔIL≤0.3
Drop-off test (drop-off height4m, once per direction, totally 3 times)	dB	ΔIL≤0.3

Environmental performance requirements:

Category	Specification			
	Condition	IL Variation	RL Variation	Appearance
High TEMP	85℃, 96H	≤0.3	≤5	No mechanical damage, like deformation, cracking and untight
Low TEMP	-40℃, 96H	≤0.3	≤5	
Temperature Cycle	Cycle: 8 hours Total: 12 cycles / 96 hours Temperature Maintenance: 1 hour	≤0.3	≤5	
Temperature/ Humidity	85℃, 95%RH, 96H	≤0.3	≤5	
Immersion	25℃, 96H	≤0.3	≤5	
Salt Mis	5% Nacl, 6.5 < PH < 7.5, 35℃, 96H	≤0.3	≤5	

Mechanical Performance Requirement


Category	Specification			
	Condition	IL Variation	RL Variation	Appearance
Impact	Height: 4m; 1 drop each axis; 3 cycles	≤ 0.3	≤ 5	No mechanical damage, like deformation, cracking and untight
Vibration	Frequency: 10 ~ 50HZ; Sweep: 45 times / min; amplitude: 0.75mm; Duration: 30min each axial	≤ 0.3	≤ 5	
Torsional	Pull: 15N; The distance between Loading location and fast connector: L = 22-28cm; Rate: 10times / min. Times:	≤ 0.3	≤ 5	
Tensile	Pull: 50N; The distance between Loading location and fast connector: L = 3M; Duration: 1min	≤ 0.3	≤ 5	

Product Packaging Information:

Blister Box Packing

	Size(CM)	14.5*7*1.5
	QTY(PCS/Box)	10
	N.W(G/PCS)	3.15
	N.W(G/Box)	31.5
	G.W(G/Box)	40

Adapter (supports strip and cut fiber):



1 adapter / 50 fast connectors



1 Operation Manual/ 10 fast connectors

Cleave fiber:



Gift Box Packing(Inner packing):

	Size(CM)	15.5*11.5*7.5
	QTY(Blister Box/Girt Box)	10
	N.W(G/Box)	273
	G.W(G/Box)	400

Outer Packing:

	Size(CM)	41*17*24.5
	QTY(Gift Box/Box)	10
	QTY(Pcs/Box)	1000
	N.W(KG/Box)	2.8
	G.W(KG/Box)	4.5
	Size(CM)	41*32*24.5
	QTY(Gift Box/Box)	20
	QTY(Pcs/Box)	2000
	N.W(KG/Box)	5.6
	G.W(KG/Box)	9.0